

WINK® WALLCOVERINGS

PRODUCT SPECIFICATIONS



Please refer to the *Installation and Maintenance Guidelines* for each product for more details.

Standard Roll	26.6 ft long x 4 ft wide (<i>Scribe/Projection</i> : 12.6 lbs; <i>Magnetic/Complete</i> : 26.46 lbs)
Coverage	Approximately 107 square feet
Characteristics	<ul style="list-style-type: none">—Superior writing and dry-erase performance, made for long term use—Smooth, white surface (<i>Scribe/Magnetic</i>: high gloss; <i>Projection/Complete</i>: low sheen)—Low Volatile Organic Compound (VOC) content, compliant with Cal 01350—Non-ghosting and non-staining PET (polyethylene terephthalate) film surface—<i>Scribe/Projection</i>: Class A fire rating as per ASTM E84; <i>Magnetic/Complete</i>: Class B
Applications	Apply to smooth surfaces including painted drywall, chalkboard, plaster, wood, and metal. <i>Scribe/Projection</i> : Heavy duty clay or clear adhesives should be used; <i>Magnetic/Complete</i> : Extreme tack, vinyl over vinyl adhesives should be used. Refer to <i>Installation and Maintenance Guidelines</i> for more details.
Preparation	Surface should be dry, prepared to Level 4 or 5 smoothness, and free of grease, mildew, dust, foreign contaminants, and any imperfections. Absorbent surfaces should be treated with a high quality, white, stain-blocking primer. Please refer to the <i>Installation and Maintenance Guidelines</i> for more details. Scuff sanding is recommended for high-gloss surfaces.
Cure Time	<i>Scribe/Projection</i> : allow 24 hours for adhesive to fully dry; <i>Magnetic/Complete</i> : allow 48 hours
Environmental Attributes	<ul style="list-style-type: none">—All wallcoverings are free of heavy metals, isocyanates, perfluorinated compounds, and toxic phthalates; <i>Scribe/Projection</i>: also PVC free; <i>Magnetic/Complete</i>: contain some PVC in magnetic material underneath the exposed layers—Low VOC content, consistent with Greenguard standards—PET film surface is formulated with up to 25% recycled content and PVC free—Qualifies for contribution to LEED v4 for Low Emitting Materials
Writing/Drawing	Most new standard dry erase markers can be used on the Wink wallcovering surface
Cleaning	For daily erasing and cleaning, use a clean microfiber cloth. On a weekly basis, use a mild dry-erase cleaner or a mixture of gentle dish soap and water with a microfiber cleaning cloth. Cleaning products containing harsh solvents or alcohol should not be used. See Care and Maintenance guidelines.
Warranty	5-year limited warranty from date of shipment
Manufacturer	Innovative Chemical Products